

All-Purpose Cleaners and Specialty Machines

Commercial Equipment



Micro Cleaner™

All-Purpose Cleaner

- Compact and maneuverable
- Unique spray only design utilizes micro fiber mops for water pick-up
- 20 gallon solution tank
- 150 psi application flow
- Onboard storage for standard accessories
- 2 chemical metering system with universal chemical storage
- Removable pallet contains all electrical components



All Cleaner™

All-Purpose Cleaner

- Compact and maneuverable
- 20 gallon solution and 12 gallon recovery tanks
- 2 chemical metering system with universal chemical storage
- 200 psi application flow
- Optional front mount squeegee for easy water pick-up
- Simple storage for recovery and solution hose
- Removable pallet contains all electrical components



Reel Cleaner®

All-Purpose Cleaner

- 25 gallon clean water tank
- 22 gallon recovery tank
- Unique reels provide ease of hose storage
- 300 psi solution spray adjusts down for chemical application
- Onboard storage for standard accessories
- Any shape chemical bottle fits on the machine
- Clean water gauge for emptying and monitoring tank
- Clam-shell design for ease of servicing
- 2 chemical metering system
- Low profile and compact design for ease of transporting

Increases productivity by 300% compared to manual wipe-downs.



By Hand
27
minutes



With Advance Reel Cleaner®
9
minutes



Adphibian™

Multi-Surface Extractor-Scrubber

- Full function extractor and scrubber with AXP™ Onboard Detergent Dispensing System
- Single deck, less than 30 seconds to change from extracting to scrubbing
- CRI SOA Approved Deep Cleaning Extractor in both LIFT™ low-moisture and restoration cleaning modes
- LIFT™ Technology for low-moisture cleaning
- Dual, anti-microbial counter rotating brushes with debris collection hopper
- Brushes, squeegee and vacuum shoes are removable without tools



HydroDry™

Dryer

- Durable rotocast Polyethylene stackable blower with a 0.5 hp motor
- 3 speed settings to select the right amount of air movement
- Blower can be angled in three different positions to direct air as needed
- 25 foot power cord to reach those distant outlets



Dust Magnet™

Dry Dust Mopping System

- Dry dusting system uses disposable dusting sheets
- Super lightweight aluminum system
- Simple static electricity attracts dust and holds it
- 23, 46 and 59 inch wide cleaning path options
- Sheets come in convenient pre-cut boxes of 200, or a continuous roll of 100 sheets



LIFT™ low-moisture technology utilizes a patented indirect spray feature that provides superior cleaning while increasing per tank productivity and reducing water consumption. Operators will experience faster dry times and true cleaning with LIFT™ technology.



Smart cleaning.

A Nilfisk-Advance Brand

Technical Specifications

Models	Micro Cleaner™	All Cleaner™	Reel Cleaner®
Solution Tank	20 gal (75.7 L)	20 gal (75.7 L)	25 gal (95 L)
Recovery Tank	–	12 gal (45.42 L)	22 gal (83 L)
Application Flow	150 psi 0.75 gpm (2.8 L/min)	200 psi 0.75 gpm (2.8 L/min)	300 psi @ nozzle, 1 gpm (4 L/min)
Vacuum Motor	–	2 stage, 900 W	3 stage, 12 amp, 1,400 W
Waterlift	N/A	81 in (206 cm)	117 in (297 cm)
Air Flow	N/A	97 cfm (2,747 L/min)	100 cfm (2,832 L/min)
Solution Hose Length	15 ft (4.57 m)	15 ft (4.57 m)	50 ft (15.25 m)
Recovery Hose Length	–	15 ft (4.57 m)	40 ft (12 m) Stretch
Blower Hose	–	13 ft (3.96 m) optional	13 ft (4 m)
Power Cord	25 ft yellow (7.62 m) w/GFI	25 ft yellow (7.62 m) w/GFI	50 ft yellow (15.25 m) w/GFCI
Rear Wheels	2 - 10 in (25 cm)	2 - 10 in (25 cm)	2 - 10 in (25 cm)
Front Casters	2 - 4 in (10 cm)	2 - 4 in (10 cm)	2 - 4 in (10 cm) w/brake
Height	38.5 in (97.8 cm)	38.5 in (97.8 cm)	40 in (101 cm)
Length	34 in (86.4 cm)	34 in (86.4 cm)	36 in (91 cm)
Width	20 in (50.8 cm)	20 in (50.8 cm)	21 in (53 cm)
Weight	64 lb (29 kg)	92 lb (41.7 kg)	135 lb (61.2 kg)

Models	Adphibian™
Solution Tank	20 gal (76 L)
Solution Pump	100 psi diaphragm demand
Flow Rates	
Hard Floor Mode	0.26 gpm (1 L/min)
Restoration Mode	0.81 gpm (3.1 L/min)
LIFT™ Mode	0.26 gpm (1 L/min)
Deep Treat™ Pre-Spray Mode	0.92 gpm (3.5 L/min)
Recovery Tank	16 gal (61 L)
Vacuum Motor	Dual 3 stage bypass
Air Flow	93 cfm (44 L/sec) (Extraction) / 67 cfm (32 L/sec) (Scrubbing)
Waterlift	70 in H ₂ O (17.4 km/hr)
Vacuum Shoes	Dual 13.5 in (34 cm) dual pivoting laminar flow 45 lb down pressure
Squeegee	36 in (91 cm) curved laminar flow
Brushes	Dual 24 in (61 cm) counter rotating anti- microbial, multi-surface with debris hopper
Brush Motors	Dual 1/2 horsepower permanent magnet
Brush Speed	960 RPM
Sound Level	69 dB A (Extraction) / 66 dB A (Scrubbing)
Electrical System	24 V (4) X 6 V batteries
Batteries	250 Ah wet-acid (optional 255 Ah AGM)
Machine Speed	
Hard Floor Mode	220 ft/min (4 km/hr)
Transport	220 ft/min (4 km/hr)
LIFT™ Mode	90 ft/min (1.6 km/hr)
Restoration Mode	50 ft/min (0.9 km/hr)
Light Deep Treat™ Mode	150 ft/min (2.7 km/hr)
Heavy Deep Treat™ Mode	100 ft/min (1.8 km/hr)
Coverage Rate	10,800 ft ² /hour (LIFT™ Mode) 6,000 ft ² /hour (Restoration Mode) 26,000 ft ² /hour (Hard Floor Mode)
CRI Approval	Bronze for Deep Cleaning Extractors in both Restoration Mode and LIFT™ Mode
Machine Dimensions	L = 56 in (142 cm) x W (without squeegee) = 27 in (69 cm) x H = 43.5 in (110 cm)
Machine Weight	650 lb (295 kg) with batteries / 370 lb (168 kg) without batteries

Models	Dust Magnet™
56 649 232	200 23 in (58 cm) Pre-Cut Sheets
56 649 231	100 Sheet Roll (perforated)
Tools and Accessories	
56 649 258	23 in (58 cm) Deluxe Aluminum Mop Holder
56 649 268	46 in (117 cm) Deluxe Aluminum Mop Holder (Wide area tool)
56 649 269	59 in (150 cm) Deluxe Aluminum Mop Holder (Extra-wide area tool)
56 649 263	39 in (99 cm) to 70 in (178 cm) Deluxe Aluminum Adjustable Shaft
56 649 267	Adjustable "Cushion Grip" Shaft
56 649 266	Speed Duster Shaft
56 649 265	59 in (150 cm) Non-adjustable aluminum shaft
56 649 281	Ergo Bend - Angle Adapter
56 649 260	Replaceable Foam Pads for 23 in (58 cm) Tool
56 649 241	Start-Up Kit for Combo Mop / Dust Magnet™ includes: 1-23 inch Aluminum Tool, 1-Adjustable Shaft and 25-Dust Magnet™ Sheets

Models	HydroDry™
Motor	0.5 hp (.37 kW) 3 speed 115 V / 50-60 Hz
Air flow – three settings	2,500 cfm (70.8 cmm), 2,000 cfm (56.6 cmm) and 1,600 cfm (45.3 cmm)
Housing	Rotocast Polyethylene
On/Off Switch	4 position
Power Cord	25 ft (7.6 m)
Weight	35 lb (15.9 kg)

Specifications are subject to change without notice.

14600 21st Avenue North
Plymouth, MN 55447-3408
www.advance-us.com
Phone 800-850-5559
Fax 800-989-6566

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.nifisk-advance.com
Phone 800-668-8400
Fax 800-263-5111



©2010 Nilfisk-Advance, Inc. Form L1604A 3-15-10

