

Floor Machines

Commercial Equipment



Pacesetter™ **13/17/20/17HD/20HD/20SD**

Floor Machines

- 13, 17 and 20 have 1.0 hp, 66 frame motors at 175 rpm
- 17HD and 20HD have 1.5 hp, 66 frame motors at 175 rpm
- 20SD is 20 inches with 1.75 hp, 66 frame motor at 175 rpm
- Ergonomic molded handles for safety and comfort
- Pad driver included



Pacesetter™ 20TS

Two-Speed Floor Machine

- Versatile 20 inch two-speed floor machine
- 1.5 hp DC motor
- 66 frame motors run at 180 and 320 rpm
- Ergonomic molded handles for safety and comfort
- Pad driver included



All-Purpose Matador™ 20

Floor Machine

- 285 rpm is ideal for a wide variety of applications
- Durable PowerFlex™ belt driven transmission
- Powered by a 1.5 hp DC rectified motor
- Built-in 3 gallon solution tank provides extra down pressure and facilitates spray buffing
- Convenient finger tip handle adjustment and solution control
- Pad driver included

Smart cleaning.

A Nilfisk-Advance Brand



Technical Specifications

Models	All-Purpose Matador™ 20	Pacesetter™ 13	Pacesetter™ 17	Pacesetter™ 20
Pad/Brush Diameter	20 in (51 cm)	13 in (33 cm)	17 in (43.2 cm)	20 in (50.8 cm)
RPM	285	175	175	175
Motor	1.5 hp DC Rectified	1.0 hp AC	1.0 hp AC	1.0 hp AC
Motor Frame Size	N/A	66	66	66
Transmission	Power-Flex Belt Driven All Metal	Dual Planetary Gears - All Metal	Dual Planetary Gears - All Metal	Dual Planetary Gears -
Amp Rating	15	12.6	12.6	12.6
Voltage/Frequency	115 V/60 Hz	120 V/60 Hz	120 V/60 Hz	120 V/60 Hz
Capacitors	N/A	Dual Start and Run	Dual Start and Run	Dual Start and Run
Cord	50 ft (15.25 m)	50 ft (15.25 m)	50 ft (15.25 m)	50 ft (15.25 m)
Weight	107 lb (49 kg)	81 lb (37 kg)	90 lb (41 kg)	93 lb (42 kg)
Pad Holder Included	Yes	Yes	Yes	Yes
Safety Switch	Yes	Yes	Yes	Yes
Approvals	ETL / Warnock Hersey	ETL / CSA	ETL / CSA	ETL / CSA

Models	Pacesetter™ 17HD	Pacesetter™ 20HD	Pacesetter™ 20SD	Pacesetter™ 20TS
Pad/Brush Diameter	17 in (43.2 cm)	20 in (50.8 cm)	20 in (50.8 cm)	20 in (50.8 cm)
RPM	175	175	175	175
Motor	1.5 hp AC	1.5 hp AC	1.75 hp AC	1.5 hp DC Rectified
Motor Frame Size	66	66	66	66
Transmission	Dual Planetary Gears - All Metal	Triple Planetary Gears - All Metal	Triple Planetary Severe Duty Gears Box	Triple Planetary Gears - All Metal
Amp Rating	15	15	15	15
Voltage/Frequency	120 V/60 Hz	120 V/60 Hz	120 V/60 Hz	120 V/60 Hz
Capacitors	Dual Start and Run	Dual Start and Run	Dual Start and Run	N/A
Cord	50 ft (15.25 m)	50 ft (15.25 m)	50 ft (15.25 m)	50 ft (15.25 m)
Weight	100 lb (45 kg)	102 lb (46 kg)	102 lb (46 kg)	87 lb (40 kg)
Pad Holder Included	Yes	Yes	Yes	Yes
Safety Switch	Yes	Yes	Yes	Yes
Approvals	ETL, CSA	ETL, CSA	ETL, CSA	ETL, CSA

Specifications are subject to change without notice.



©2009 Nilfisk-Advance, Inc. Form L1606A 4-14-09

14600 21st Avenue North
Plymouth, MN 55447-3408
www.advance-us.com
Phone 800-850-5559
Fax 800-989-6566

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.nilfisk-advance.com
Phone 800-668-8400
Fax 800-263-5111

