

SPECIALTY MACHINES

DEFINING CLEANING INNOVATION



COMMERCIAL EQUIPMENT



Advance Micro Cleaner™

All-Purpose Cleaner

- Compact and maneuverable
- Unique spray only design utilizes micro fiber mops for water pick-up
- 20 gallon solution tank
- 150 psi application flow
- Onboard storage for standard accessories
- 2 chemical metering system with universal chemical storage
- Removable pallette contains all electrical components



Advance All Cleaner™

All-Purpose Cleaner

- Compact and maneuverable
- 20 gallon solution and 12 gallon recovery tanks
- 2 chemical metering system with universal chemical storage
- 200 psi application flow
- Optional front mount squeegee for easy water pick-up
- Simple storage for recovery and solution hose
- Removable pallette contains all electrical components



Advance Reel Cleaner®

All-Purpose Cleaner

- 25 gallon clean water tank
- 22 gallon recovery tank
- Unique reels provide ease of hose storage
- 300 psi solution spray adjusts down for chemical application
- Onboard storage for standard accessories
- Any shape chemical bottle fits on the machine
- Clean water gauge for emptying and monitoring tank
- Clam-shell design for ease of servicing
- 2 chemical metering system
- Low profile and compact design for ease of transporting

Increases productivity by 300% compared to manual wipe-downs.



By Hand
27
minutes



With Advance Reel Cleaner®
9
minutes



Advance Adphibian™

Multi-Surface Extractor-Scrubber

- Full function extractor and scrubber with AXP™ Onboard Detergent Dispensing System
- Single deck, less than 30 seconds to change from extracting to scrubbing
- CRI SOA Approved Deep Cleaning Extractor in both LIFT™ low-moisture and restoration cleaning modes
- LIFT™ Technology for low-moisture cleaning
- Dual, anti-microbial counter rotating brushes with debris collection hopper
- Brushes, squeegee and vacuum shoes are removable without tools



LIFT low-moisture technology utilizes a patented indirect spray feature that provides superior cleaning while increasing per tank productivity and reducing water consumption. Operators will experience faster dry times and true cleaning with LIFT technology.



Advance HydroDry™

Dryer

- Durable rotocast Polyethylene stackable blower with a 0.5 hp motor
- 3 speed settings to select the right amount of air movement
- Blower can be angled in three different positions to direct air as needed
- 25 foot power cord to reach those distant outlets

SPECIALTY MACHINES

DEFINING CLEANING INNOVATION



SPECIFICATIONS

MODELS:	Micro Cleaner™	All Cleaner™	Reel Cleaner®
Solution Tank	20 gal (75.7 L)	20 gal (75.7 L)	25 gal (95 L)
Recovery Tank	–	12 gal (45.42 L)	22 gal (83 L)
Application Flow	150 psi 0.75 gpm (2.8 L/min)	200 psi 0.75 gpm (2.8 L/min)	300 psi @ nozzle, 1 gpm (4 L/min)
Vacuum Motor	–	2 stage, 900 W	3 stage, 12 amp, 1,400 W
Waterlift	N/A	81 in (206 cm)	117 in (297 cm)
Air Flow	N/A	97 cfm (2,747 L/min)	100 cfm (2,832 L/min)
Solution Hose Length	15 ft (4.57 m)	15 ft (4.57 m)	50 ft (15.25 m)
Recovery Hose Length	–	15 ft (4.57 m)	40 ft (12 m) Stretch
Blower Hose	–	13 ft (3.96 m) optional	13 ft (4 m)
Power Cord	25 ft yellow (7.62 m) w/GFI	25 ft yellow (7.62 m) w/GFI	50 ft yellow (15.25 m) w/GFCI
Rear Wheels	2 - 10 in (25 cm)	2 - 10 in (25 cm)	2 - 10 in (25 cm)
Front Casters	2 - 4 in (10 cm)	2 - 4 in (10 cm)	2 - 4 in (10 cm) w/brake
Height	38.5 in (97.8 cm)	38.5 in (97.8 cm)	40 in (101 cm)
Length	34 in (86.4 cm)	34 in (86.4 cm)	36 in (91 cm)
Width	20 in (50.8 cm)	20 in (50.8 cm)	21 in (53 cm)
Weight	64 lb (29 kg)	92 lb (41.7 kg)	135 lb (61.2 kg)

MODELS:	Adphibian™	MODELS:	HydroDry™
Solution Tank	20 gal (76 L)	Motor	0.5 hp (.37 kW) 3 speed 115 V/50-60 Hz
Solution Pump	100 psi diaphragm demand	Air flow – three settings	2,500 cfm (70.8 cmm)
Flow Rates			2,000 cfm (56.6 cmm)
Hard Floor Mode	0.26 gpm (1 L/min)		1,600 cfm (45.3 cmm)
Restoration Mode	0.81 gpm (3.1 L/min)	Housing	Rotocast Polyethylene
LIFT™ Mode	0.26 gpm (1 L/min)	On/Off Switch	4 position
Deep Treat™ Pre-Spray Mode	0.92 gpm (3.5 L/min)	Power Cord	25 ft (7.6 m)
Recovery Tank	16 gal (61 L)	Weight	35 lb (15.9 kg)
Vacuum Motor	Dual 3 stage bypass		
Air Flow	93 cfm (44 L/sec) (Extraction) / 67 cfm (32 L/sec) (Scrubbing)		
Waterlift	70 in H ₂ O (17.4 km/hr)		
Vacuum Shoes	Dual 13.5 in (34 cm) dual pivoting laminar flow 45 lb down pressure		
Squeegee	36 inch (91 cm) curved laminar flow		
Brushes	Dual 24 in (61 cm) counter rotating anti-microbial, multi-surface with debris hopper		
Brush Motors	Dual 1/2 horsepower permanent magnet		
Brush Speed	960 RPM		
Sound Level	69 dB A (Extraction) / 66 dB A (Scrubbing)		
Electrical System	24 V (4) X 6 V batteries		
Batteries	250 Ah wet-acid (optional 255 Ah AGM)		
Machine Speed			
Hard Floor Mode	220 ft/min (4 km/hr)		
Transport	220 ft/min (4 km/hr)		
LIFT™ Mode	90 ft/min (1.6 km/hr)		
Restoration Mode	50 ft/min (0.9 km/hr)		
Light Deep Treat™ Mode	150 ft/min (2.7 km/hr)		
Heavy Deep Treat™ Mode	100 ft/min (1.8 km/hr)		
Coverage Rate	10,800 ft ² /hour (LIFT™ Mode) 6,000 ft ² /hour (Restoration Mode) 26,000 ft ² /hour (Hard Floor Mode)		
CRI Approval	Bronze for Deep Cleaning Extractors in both Restoration Mode and LIFT™ Mode		
Machine Dimensions	L = 56 in (142 cm) x W (without squeegee) = 27 in (69 cm) x H = 43.5 in (110 cm)		
Machine Weight	650 lb (295 kg) with batteries / 370 lb (168 kg) without batteries		



14600 21st Avenue North
Plymouth, MN 55447-3408
www.advance-us.com
Phone: 800-850-5559
Fax: 800-989-6566

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.nilfisk-advance.com
Phone: 905-564-1149 or 800-668-8400
Fax: 905-564-1030 or 800-263-5111

©2009, Nilfisk-Advance, Inc., Printed in U.S.A., Form L1604A 1/09



recyclable