

# Portable Extractors

## Commercial Equipment



### ET610™

#### Portable Extractors

- 12.5 gallon solution tank
- 11 gallon recovery tank
- Single 5.7 inch, 3-stage vacuum motor
- 140 inch waterlift (100SC and 100H)
- 1,100 Watt heater (100SC) and 1,750 Watt heater (100H)
- Cold water extractor (100C)
- Ergonomic design
- 12 inch stainless steel wand standard (AquaWand™ optional upgrade)
- Wand caddy for easy transport
- Unique transport handle design
- Easy-fill solution tank
- Low moisture / environmental footprint reduction system



### ET700™

#### Heated Portable Extractor

- 12 gallon solution tank
- 10 gallon recovery tank
- Dual 5.7 inch, 3-stage vacuum motor
- 200 inch waterlift
- 50-500 psi
- 2,000 Watt heater
- In-line heater element
- Smart circuit locator
- AquaWand™ standard
- Low moisture system
- Day-time-quiet operation
- Roller handles for easy loading
- Upright dolly design for easy stair climbing
- Wand caddy for easy transport
- Low solution filling area for easy filling



### AquaSpot®

#### Carpet Spot Extractor

- A clear recovery tank with 2 dumping ports allows for ease of cleaning
- Exhaust air is filtered for maintaining indoor air quality
- Optional cart is designed with a tray and holds cleaning accessories



Smart cleaning.

## Technical Specifications

Models	AquaSpot®	ET610™ 100C	ET610™ 100SC	ET610™ 100H	ET700™
Solution Tank	2 gal (7.6 L)	12.5 gal (47.3 L)	12.5 gal (47.3 L)	12.5 gal (47.3 L)	12 gal (45.4 L)
Recovery Tank	2 gal (7.6 L)	11 gal (41.6 L)	11 gal (41.6 L)	11 gal (41.6 L)	10 gal (37.9 L)
Pump Pressure	38 psi (2.62 bar)	100 psi, diaphragm pump,	100 psi, diaphragm pump,	100 psi, diaphragm pump,	500 psi, diaphragm pump
Solution Flow Rate	0.3 gpm (1.1 L/min)	0.8 gpm (3 L/min)	0.8 gpm (3 L/min)	0.8 gpm (3 L/min)	0.8 gpm (3 L/min)
Built-in Heater	–	–	1,100 W	1,750 W	1,750 W
Vacuum Motor	1 hp	Single 5.7 in	Single 5.7 in	Single 5.7 in	Dual 5.7 in
Vacuum Motor Stages	2 stage	3 stage	3 stage	3 stage	3 stage
Waterlift	79 in (200 cm)	–	140 in (355.6 cm)	140 in (355.6 cm)	200 in (508 cm)
Airflow	88 cfm	100 cfm	100 cfm	100 cfm	–
Solution Hose Length	9 ft (2.7 m)	15 ft (4.5 m)	15 ft (4.5 m)	15 ft (4.5 m)	15 ft (4.5 m)
Vacuum Hose Length	8 ft (2.4 m)	15 ft (4.5 m)	15 ft (4.5 m)	15 ft (4.5 m)	15 ft (4.5 m)
Vacuum Tool Length	3.5 in (9 cm)	12 in (30.5 cm)	12 in (30.5 cm)	12 in (30.5 cm)	12 in (30.5 cm)
Power Cable	25 ft (7.6 m) detachable	25 ft (7.6 m) detachable	25 ft (7.6 m) detachable	25 ft (7.6 m) detachable	25 ft (7.6 m) detachable
Height	17 in (43 cm)	40.5 in (103 cm)	40.5 in (103 cm)	40.5 in (103 cm)	33 in (84 cm)
Length	20 in (51 cm)	42 in (107 cm)	42 in (107 cm)	42 in (107 cm)	39 in (100 cm)
Width	9 in (23 cm)	21 in (54 cm)	21 in (54 cm)	21 in (54 cm)	25 in (64 cm)
Weight	20 lb (9 kg)	87 lb (40 kg)	87 lb (40 kg)	87 lb (40 kg)	110 lb (50 kg)

Specifications are subject to change without notice.

9435 Winnetka Avenue North  
 Brooklyn Park, MN 55445  
[www.advance-us.com](http://www.advance-us.com)  
 Phone 800-850-5559  
 Fax 800-989-6566

240 Superior Boulevard  
 Mississauga, Ontario, Canada L5T 2L2  
[www.nilfisk-advance.com](http://www.nilfisk-advance.com)  
 Phone 800-668-8400  
 Fax 800-263-5111



©2017 Nilfisk, Inc. Form L1603A 2-14-17



[www.advance-us.com](http://www.advance-us.com)