

# Wet/Dry Tank Vacuums

## Commercial Equipment



### **AWD w/ and w/o Air Scoop™**

Wet/Dry Tank Vacuums

- Available in 20 and 15 gallon sizes, with compact footprint to take up minimal room in tight spaces
- Front mount squeegee optional in 24 inch or 30 inch sizes
- Adjustable handle folds over machine for easy transport
- Optional H.E.P.A. filtration available



### **Sprite® Air Scoop™ 16**

Wet/Dry Tank Vacuum

- 16 gal tank capacity
- 24 inch front mount squeegee standard, tools are separate
- 1.3 hp 2 stage motor, waterlift 88 inch, 91 CFM, 73 dB A
- Empty by tip-and-pour or front drain hose, 50 foot cord
- Removable tank for easy cleaning

Smart cleaning.

A Nilfisk-Advance Brand



## Technical Specifications

Models	AWD-315	AWD-320	Sprite® Air Scoop™ 16
Nominal Voltage/Hz	120 V/60 Hz	120 V/60 Hz	115 V/60 Hz
Rated Power	1,350 W	1,350 W	800 W
Recoverable Capacity	15 gal (56.7 L)	20 gal (75.7 L)	16 gal (60 L)
Air Flow	130 CFM (61.3 L/sec)	130 CFM (61.3 L/sec)	91 CFM (43 L/sec)
Waterlift	95 in (241 cm)	95 in (241 cm)	88 in (2.2 m)
Front Mount Squeegee	Optional	Optional	Standard
Sound Pressure Level	68 dB A	68 dB A	73 dB A
Dry Dust Collection	In Tank and Optional Dust Bag	In Tank and Optional Dust Bag	Optional Bag
Std Filtration Level	2 Optional to 5	2 Optional to 5	1
H.E.P.A. Filtration	Optional	Optional	No
Weight w/Electric Cord	42 lb (19 kg)	45 lb (20.4 kg)	77 lb (35 kg)
Power Cable Length	50 ft (15 m)	50 ft (15 m)	50 ft (15 m)
Length	30.5 in (77 cm)	35 in (89 cm)	40 in (102 m)
Width	17 in (43 cm)	17 in (43 cm)	17 in (43 cm)
Height	19 in (48 cm)	19 in (48 cm)	39.5 in (100 cm)

Specifications are subject to change without notice.



recyclable

©2010 Nilfisk-Advance, Inc. Form L1605A 8-6-10

14600 21st Avenue North  
Plymouth, MN 55447-3408  
www.advance-us.com  
Phone 800-850-5559  
Fax 800-989-6566

240 Superior Boulevard  
Mississauga, Ontario, Canada L5T 2L2  
www.nilfisk-advance.com  
Phone 800-668-8400  
Fax 800-263-5111

