Portable Extractors

Commercial Equipment





CERTIFIED BRONZE

EX610™ 100H

ET610™

Portable Extractors

- 12.5 gallon solution tank
- 11 gallon recovery tank
- Single 5.7 inch, 3-stage vacuum motor
- 140 inch waterlift (100SC and 100H)
- 212° heat at wand tip (100SC and 100H models)
- Cold water extractor (100C)
- Ergonomic design
- 12 inch stainless steel wand standard (AquaWand™ optional upgrade)
- Wand caddy for easy transport
- Unique transport handle design
- Easy-fill solution tank
- Low moisture / environmental footprint reduction system



CERTIFIED GOLD

ET700™

Heated Portable Extractor

- 12 gallon solution tank
- 10 gallon recovery tank
- Dual 5.7 inch, 3-stage vacuum motor
- 200 inch waterlift
- 50-500 psi
- 2,000 Watt heater
- In-line heater element
- Instant heat up to 212° F at the wand tip
- Smart circuit locator
- AquaWand™ standard
- Low moisture system
- Day-time-quiet operation
- Roller handles for easy loading
- Upright dolly design for easy stair climbing
- Wand caddy for easy transport
- Low solution filling area for easy filling



AquaSpot®

Carpet Spot Extractor

- A clear recovery tank with 2 dumping ports allows for ease of cleaning
- Exhaust air is filtered for maintaining indoor air quality
- Optional cart is designed with a tray and holds cleaning accessories

Advance

Smart cleaning.

Technical Specifications

Models	AquaSpot®	ET610™ 100C	ET610™ 100SC	ET610™ 100H	ET700™
Solution Tank	2 gal (7.6 L)	12.5 gal (47.3 L)	12.5 gal (47.3 L)	12.5 gal (47.3 L)	12 gal (45.4 L)
Recovery Tank	2 gal (7.6 L)	11 gal (41.6 L)	11 gal (41.6 L)	11 gal (41.6 L)	10 gal (37.9 L)
Pump Pressure	38 psi (2.62 bar)	100 psi, diaphragm pump,	100 psi, diaphragm pump,	100 psi, diaphragm pump,	500 psi, diaphragm pump
Solution Flow Rate	0.3 gpm (1.1 L/min)	0.8 gpm (3 L/min)	0.8 gpm (3 L/min)	0.8 gpm (3 L/min)	0.8 gpm (3 L/min)
Built-in Heater	–	–	1,100 W, 212° F	1,750 W, instant 212° F	1,750 W, instant 212° F
Vacuum Motor	1 hp	Single 5.7 in	Single 5.7 in	Single 5.7 in	Dual 5.7 in
Vacuum Motor Stages	2 stage	3 stage	3 stage	3 stage	3 stage
Waterlift	79 in (200 cm)	–	140 in (355.6 cm)	140 in (355.6 cm)	200 in (508 cm)
Airflow	88 cfm	100 cfm	100 cfm	100 cfm	–
Solution Hose Length	9 ft (2.7 m)	15 ft (4.5 m)	15 ft (4.5 m)	15 ft (4.5 m)	15 ft (4.5 m)
Vacuum Hose Length	8 ft (2.4 m)	15 ft (4.5 m)	15 ft (4.5 m)	15 ft (4.5 m)	15 ft (4.5 m)
Vacuum Tool Length	3.5 in (9 cm)	12 in (30.5 cm)	12 in (30.5 cm)	12 in (30.5 cm)	12 in (30.5 cm)
Power Cable	25 ft (7.6 m) detachable	25 ft (7.6 m) detachable	25 ft (7.6 m) detachable	25 ft (7.6 m) detachable	25 ft (7.6 m) detachable
Height	17 in (43 cm)	40.5 in (103 cm)	40.5 in (103 cm)	40.5 in (103 cm)	33 in (84 cm)
Length	20 in (51 cm)	42 in (107 cm)	42 in (107 cm)	42 in (107 cm)	39 in (100 cm)
Width	9 in (23 cm)	21 in (54 cm)	21 in (54 cm)	21 in (54 cm)	25 in (64 cm)
Weight	20 lb (9 kg)	87 lb (40 kg)	87 lb (40 kg)	87 lb (40 kg)	110 lb (50 kg)

Specifications are subject to change without notice.

9435 Winnetka Avenue North
Brooklyn Park, MN 55445
www.advance-us.com
Phone 800-850-5559
Fax 800-989-6566

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.nilfisk-advance.com
Phone 800-668-8400
Fax 800-263-5111

recyclable

©2015 Nilfisk, Inc. Form L1603A 10-12-15

Advance