

VU500™ Series

12 & 15 inch Upright Vacuums



The Advance VU500™ delivers exceptional cleaning performance in an easy to use, easy to maintain upright vacuum that is designed to withstand stringent environmental requirements.

- Automatic, self-adjusting brush height makes it easy to transition between different floor surfaces
- Unique design features provide exceptional maneuverability in tight spaces, increasing operator efficiency
- Three-stage filtration system with true H.E.P.A. filtration traps at least 99.97% of dust, pollen, mold, bacteria and other airborne particles ≥ .3 microns, improving indoor air quality for greater occupant comfort
- Meets LEED requirements with CRI Seal of Approval (Silver) and low sound levels





VU500™ Series

12 & 15 inch Upright Vacuums

Taking Ease of Use to the Next Level



Radius Turning System permits quick, short turns in tight places



Detachable power cable for quick service



Innovative quick cord clip for simple cord management



Indicator light shows when bag is full or vacuum is clogged



Industry-leading three-stage sealed H.E.P.A. filtration removes 99.97% of all particles >0.3 microns for improved IAQ



Easy access to clogs, minimizing potential downtime



resistant bumper

Technical Specifications

Model	VU500™12 inch	VU500™15 inch
Vacuum Motor	120 V, 60 Hz, 1,000 W, 9 amp, 2-stage – BOTH MODELS	
Motor Protection	Airflow bypass valve and thermal overload protection – BOTH MODELS	
Suction (waterlift) / Airflow	92 in / 93 cfm — BOTH MODELS	
Brush	Dual row, chevron style, nylon with auto adjustment – BOTH MODELS	
Brush Speed	2,800 RPM – BOTH MODELS	
Cleaning Path	11.5 in (29.2 cm)	14.5 in (36.7 cm)
Filtration	2-ply paper filter bag, motor pre-filter, certified H.E.P.A. exhaust filter	
Bag Capacity	3.4 qt (3.2 L) — BOTH MODELS	
Power Cable	33 ft (10 m) 18/3 wire gray, detachable	50 ft (15 m) 18/3 wire gray, detachable
Sound Level	68 dB A – BOTH MODELS	
Onboard Tools	4:1 stretch hose, wand, crevice tool, spare filter bag - BOTH MODELS	
Optional Tools	Upholstery tool, dusting tool, tool clip – BOTH MODELS	
Dimensions (LxWxH)	13.25 in x 12.5 in x 46.5 in (33 cm x 31.8 cm x 118 cm)	13.25 in x 15.25 in x 46.5 in (33 cm x 39 cm x 118 cm)
Weight (with cord)	19.5 lb (8.8 kg)	19.8 lb (9 kg)
Warranty	Motor and belts – 2 years, non-wear parts, labor – 1 year – BOTH MODELS	
Part Number	107404753	107404754
Approvals	CRI (Carpet & Rug Institute) Seal of Approval (Silver) LEED-EBOM (Leadership in Energy and Environmental Design for Existing Buildings: Operations & Maintenance – BOTH MODELS	

Specifications are subject to change without notice.









9435 Winnetka Avenue North Brooklyn Park, MN 55445 www.advance-us.com Phone 800-850-5559 Fax 800-989-6566

240 Superior Boulevard Mississauga, Ontario, Canada L5T 2L2 www.nilfisk-advance.ca Phone 800-668-8400 Fax 800-263-5111



