

# BU800™ 20B & 20BT

Battery Burnishers



## Advance

### FACT SHEET



#### **SUPERIOR SHINE. EASIER TO USE DESIGN.**

When the job calls for restoring your floor's gloss, the Advance BU800™ battery burnisher outshines even its updated look.

Operators of the BU800 will sense a whole new feel and experience when burnishing. A more rigid frame and nine vibration isolators have turned the operation of the BU800 into the smoothest burnishing experience in the market.

With an updated, double-pivot pad-driver design, the BU800 burnishing pad stays in alignment and allows the pad to follow the floor contours, leaving a more consistent gloss. Combining the pad-driver design with the self-regulating pad pressure, operators have an easy to use, battery walk-behind burnisher that saves labor time and dollars.

Adding to the ease of operation is the self-lowering burnishing deck. When the palm switches on the handle are activated, the burnishing deck automatically lowers to the floor. When the palm switches are released, the deck automatically returns to a raised position. Simple controls also minimize training time of operators.

The BU800 has a 20 inch burnishing path, and comes with either wet batteries for dependable long run time, or maintenance-free AGM gel type batteries for an even longer run time. The onboard battery charger allows for convenient charging at any 120 Volt outlet so that operators don't need to return the machine to a storage or charging area.

Safety isn't sacrificed for price and performance. An angle-activated safety switch keeps the machine from starting when tipped back in the pad change position. Superior mobility and line of site during operation add to its safety when in operation.

The best passive dust control in the market is included on all models, which contributes to improved indoor air quality during operation. A felt seal contains all dust within a specially designed shroud, directing it into a dual-port, disposable filter bag. For facilities where indoor air quality is even more critical, optional active dust control is available with the addition of an Adgility™ hip-style vacuum on the front of the machine.

The Advance BU800 battery burnisher delivers the smooth performance, consistent shine, and cleaner indoor air quality that is demanded by today's customers.

#### **ACCESSORIES AND OPTIONS**

- 20 inch burnishing path
- Wet cell or AGM batteries
- Onboard charger (standard)
- Non-traction or traction drive
- Passive dust control
- Passive vacuum paper bags
- Active vacuum paper bags
- Active vacuum cloth bag
- Aqua HS burnishing pads
- Natural blend tan HS burnishing pads
- Natural blend white HS burnishing pads
- Automatic, continuous pad alignment (standard)

#### **TYPICAL APPLICATIONS INCLUDE**

- K-12 Schools
- Colleges and Universities
- Hospitals and Healthcare Facilities
- Supermarkets
- Retail Stores and Shopping Centers
- Government Buildings



# Advance BU800™ 20B & 20BT

## Battery Burnishers



Easy to operate control panel and palm switches. Non-traction model shown.



Traction drive model features speed control and reverse button.



Two port dust bag is easy to access for bag changes.



Pad changes are easier with the tip back design of the BU800™.



Optional vacuum available for active dust control.



Choose between wet cell or service-free AGM batteries. Onboard charger is standard.



## Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factory-trained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Parts.

## Technical Specifications

Model	BU800™ 20B	BU800™ 20BT
Burnishing Path / Pad Diameter	20 in (50.8 cm)	20 in (50.8 cm)
Power	36 V, (3) 12 V batt.	36 V, (3) 12 V batt.
Drive - Traction or Non-Traction	Non-Traction	Traction
Transaxle Traction Motor	–	0.5 hp (0.371 W)
Forward Speed	–	0 - 240 ft/min (73.2 m/min)
Reverse Speed	–	0 - 170 ft/min (51.8 m/min)
Low Battery Protection	Yes	Yes
Onboard Charger	36 V, 25 A DC, 85-265 V / 45-65 Hz AC - ALL MODELS	
Pad Motor	2.5 hp (1.9 kW)	2.5 hp (1.9 kW)
Pad RPM (on the floor)	2,000 rpm	2,000 rpm
Pad Pressure	Self Regulating to 30 lb (13 kg) - ALL MODELS	
Sound Level	68 dB A	68 dB A
Drive Wheels	1.62 in x 8 in (4 cm x 20 cm) - ALL MODELS	
Polishing Rate (Maximum)	24,000 ft <sup>2</sup> /hr (7,315 m <sup>2</sup> /hr)	24,000 ft <sup>2</sup> /hr (7,315 m <sup>2</sup> /hr)
Polishing Rate (Practical)	17,600 ft <sup>2</sup> /hr (5,365 m <sup>2</sup> /hr)	17,600 ft <sup>2</sup> /hr (5,365 m <sup>2</sup> /hr)
Length	50 in (127 cm)	50 in (127 cm)
Width	23 in (58 cm)	23 in (58 cm)
Height	41.25 in (105 cm)	41.25 in (105 cm)
Batteries	200 Ah / 234 Ah AGM	200 Ah / 234 Ah AGM
Weight with Batteries	551 lb / 596 lb (250 kg) / (270 kg)	565 lb / 609 lb (256 kg) / (276 kg)
Shipping Weight	597 lb / 642 lb (271 kg) / (291 kg)	611 lb / 655 lb (277 kg) / (297 kg)
Part Number		
Passive Dust Control	56383510 / 56383512	56383509 / 56383511

Specifications are subject to change without notice.



# Advance

9435 Winnetka Avenue North  
Brooklyn Park, MN 55445  
www.advance-us.com  
Phone: 800-850-5559  
Fax: 800-989-6566

240 Superior Boulevard  
Mississauga, Ontario, Canada L5T 2L2  
www.nilfisk-advance.ca  
Phone: 905-564-1149 or 800-668-8400  
Fax: 905-564-1030 or 800-263-5111



©2015, Nilfisk, Inc.,  
Printed in U.S.A., Form L3330A, 3-15

