# Adgressor<sup>®</sup> & Adgressor<sup>®</sup> with EcoFlex<sup>™</sup> System **∂ Advance**

### **Rider Scrubbers**

## FACT SHEET



#### Flexibility for every kind of clean.

The Advance Adgressor<sup>®</sup> rider-scrubber with EcoFlex<sup>™</sup> System lets you clean green and still meet the highest expectations for clean floors. With the industry's most flexible floor-scrubber technology, you can develop a sustainable cleaning routine and quickly adjust to whatever the job demands. Be prepared to get more out of your budget, clean with less impact to the environment and maintain clean floors when you do.

Operators can quickly and easily select the right blend of pad pressure, water and detergent to tackle any cleaning challenge. Here are just a few of the flexible cleaning modes:

- *Water Only* Perfect for removing surface dirt and maintaining the clean look of floors. Water-only mode eliminates the impact of detergents on the environment and reduces cleaning costs.
- *Ultra-low Detergent* Well suited for routine cleaning where a small amount of green-certified detergent will do the trick. Water and detergent are dispensed separately at the scrub deck, eliminating solution waste.
- Standard Detergent The tough cleaning you expect. At standard detergent, pad
  pressure and flow rate, you'll have a combination powerful enough to pull stubborn
  dirt, grease, and oil from the surface.
- **Burst of Power** For deep, restorative cleaning or unexpected challenges. EcoFlex's burst of power temporarily increases your machine's pad pressure, detergent use and flow rate at the touch of a button.

The Adgressor is designed as a true industrial rider scrubber with reliability, productivity, and ease of use and maintenance built in. Combining large scrub decks and solution capacities with maneuverability and speed, the Adgressor delivers high productivity. A steel chassis and metal bumpers stand up to tough operating environments while thick rotomolded polyethylene tanks will not dent, crack, or corrode.

The Adgressor with EcoFlex System delivers the flexibility to clean your floors more efficiently. By using a system that cleans like you do, you'll reduce your cost to clean and create a more sustainable cleaning program.

#### STANDARD FEATURES INCLUDE

- QuickChange<sup>™</sup> deck system
- 42 gallon solution and recovery tanks
- Smart Solutions<sup>™</sup>
- Powerful drive motor
- One-Touch<sup>™</sup> system activation
- Metal bumpers
- Comfortable, ergonomic design
- No-tools maintenance access
- Safe Clear-View<sup>™</sup> of cleaning area
- Best-in-class maneuverability
- Mechanical brake

#### TYPICAL APPLICATIONS INCLUDE


- Large Retail/Malls
- Stadiums and Arenas
- Municipalities
- Universities
- Government Buildings
- Distribution/Warehousing
- Food and Beverage
- Light Manufacturing
- Transportation Facilities





# Adgressor<sup>®</sup> & Adgressor<sup>®</sup> with EcoFlex<sup>™</sup> System

## **Rider Scrubbers**




EcoFlex<sup>™</sup> System models have One-Touch<sup>™</sup> activation for an on-demand cleaning burst of power.



One-Touch<sup>™</sup> activation of scrub system. All systems start and stop with machine motion.

# Yange <th

The Advance Adgressor® can Grow with your company. The scrub deck interchangeability allows a larger, more productive scrub deck to be installed to address a growing company's increasing square footage.



The Advance Adgressor® turns within a 63 inch (160 cm) aisle. This improves productivity by allowing the Advance Adgressor® to easily clean smaller aisles than the competition. Comfortable full size operator Optional EcoFlex<sup>™</sup> System compartment has excellent field of vision with **Clear-View<sup>™</sup>** sight lines. flexibility.

Large recovery tank \_\_\_\_\_ opening provides easy, unobstructed cleaning.

High capacity and rugged polyethylene \_ solution and recovery tanks are crack, dent and chemical resistant.

Solution tank has — EasyFlow™ drain hose, for clean and controlled dumping.

> UltraFlow<sup>™</sup> / Unique design increases air speed in squeegee for better pick up and dryer floors.

QuickChange<sup>™</sup> no tools interchangeable deck system. One Touch<sup>™</sup> control panel for all scrub functions. Includes all indicators/gauges.

> , Variable volume horn and backup alarm are standard.

Steering column is adjustable for comfort: tilts upright for easy boarding.

Mechanical safety brake with parking brake standard.

Metal bumpers for added machine protection.

Heavy-duty side skirts leave floors dry and safe.

## Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factory-trained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Parts.

# **Technical Specifications**

	——————		
Model	Adgressor® 3220	Adgressor® 3520	Adgressor® 3820
Scrub Path	32 in (81 cm)	35 in (89 cm)	38 in (97 cm)
Max. Productivity	56,320 ft²/hr	61,600 ft²/hr	66,880 ft²/hr
at 4.0 mph			
Max. Productivity	35,200 ft²/hr	38,500 ft²/hr	41,800 ft²/hr
at 2.5 mph			
Solution Tank	42 gal (157 L)	42 gal (157 L)	42 gal (157 L)
Recovery Tank	42 gal (157 L)	42 gal (157 L)	42 gal (157 L)
Brush Drive			
Disc –	1.5 hp (1)	0.6 hp (3)	0.6 hp (3)
Cylindrical –	Two 0.75 hp, 560 Watt motors on opposing ends, poly-V belt brush drive		
Scrub Deck			
Disc –	Manual-adjusting side skirts contain solution		
Cylindrical –	Includes hopper for collecting small litter. Auto-adjusting side skirts contain solution		
Brush Speed	Disc 250 rpm, Cylindrical 900 rpm		
Brush Pressure	Programmable 3 settings up to 250 lb (113 kg)		
Drive System	1.5 hp motor with gear transmission, band brake and dynamic braking.		
	Programmable speeds up to 4.5 mph (7.3 kph)		
Gradeability	Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg		
Min. Turn-around	63 inch (160 cm) with a 32 inch deck		
Aisle Width			
Voltage	36 Volt for more power and longer run time		
Power Source	310 Ah or 420 Ah wet or 312 AGM maint-free battery options		
Battery Charger	Option of shelf or onboard charger		
Solution Control	Smart Solutions <sup>™</sup> is standard providing better water and chemical utilization and fewer dump and refill cycles.		
Vacuum Motor	0.75 hp 3-stage with optional dual vacuum		
Sound Level	68 dB A at operator's position		
Frame Dimensions	Length = 61 in (155 cm), Width = 32 in (82 cm), Height = 53 in (135 cm) – All Models		
Squeegee Width	36.6 in (93 cm)	42.1 in (107 cm)	45.1 in (115 cm)
Weight	Machine Only 657 lb (298 kg). V	Vith full tank and standard batte	eries 1,553 lb (705 kg) – All Models
Optional Adgressor® EcoFlex™ System Specifications			
Solution Flow Pump			
Dilution Ratios	32:1, 50:1, 64:1, 100:1, 128:1, 150:1, 200:1, 256:1, 300:1		
Refillable Cartridge Capacity	1.25 gal (4.75 L)		
Battery Watering System			



9435 Winnetka Avenue North Brooklyn Park, MN 55445 www.advance-us.com Phone: 800-850-5559 Fax: 800-989-6566 240 Superior Boulevard Mississauga, Ontario, Canada L5T 2L2 www.nilfisk-advance.ca Phone: 905-564-1149 or 800-668-8400 Fax: 905-564-1030 or 800-263-5111

©2016, Nilfisk, Inc.,

Specifications are subject to change without notice.

Printed in U.S.A., Form L1969A 4-16

