

Advolution™ 20 & 20XP

Cord Electric Burnishers



Advance

FACT SHEET



The Advolution™ 20 and 20XP cord-electric burnishers from Advance are designed to maximize performance, productivity, and operator ease. Both models feature the unique Flex Floor™ Technology – based on a patented, pintle-mounted motor design – that enables the motor to pivot and hug the contours of the floor's surface. The Advolution also utilizes a patented gas spring technology that precisely regulates the head pressure for a maximum shine on floor surfaces, regardless of the operator's previous burnisher experience. This exclusive patent also enables the machine to be smaller, more maneuverable, and easier to train on.

Advance had uncompromised facility safety in mind when it added a 75 foot safety yellow, SuperFlex™ cord and a hospital-grade plug. The SuperFlex™ cord is secured with a quick-release rotating cord hook, which allows the operator to release all 75 feet of the cord at once to save time and effort. Another key safety feature is the SafeStart™ function which requires the handle to be in the operating position before the machine can be started. This helps to prevent unmanned use of the burnisher. Operating at less than 67 dB A, the volume of standard conversation, the Advolution 20 & 20XP burnishers are perfect for daytime burnishing.

The space-saving EZ Store™ handle minimizes the storage space necessary for the Advolution 20 & 20XP burnishers. While in the EZ Store™ space-saving position, the operator has easy access to check wear or replace the burnishing pad.

The Advolution 20 has a 20 inch burnishing surface which runs at 1,500 rpm. The Advolution 20XP is a 20 inch dust control model that runs at 2,000 rpm. The powerful suction on the Advolution 20XP sends all of the burnishing dust into the unit's dual-port dust bag and not into the air. This provides total dust control for improved indoor air quality, while operating at higher speeds, to protect the health of the operators and facility occupants. When using the Advolution 20XP, operator productivity is increased by eliminating the need for dust mopping after burnishing.

TYPICAL APPLICATIONS INCLUDE

- Healthcare Facilities
- Hotels / Hospitality
- Schools
- Religious Facilities
- Government Facilities

STANDARD FEATURES INCLUDE

- Flex Floor Technology
- 75 foot Safety Yellow SuperFlex™ Cord
- Rotating Cord Hook
- EZ Store™ Folding Handle
- 20XP has Passive Dust Control




Advance Advolution™ 20 & 20XP

Cord Electric Burnishers

Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factory-trained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Genuine OEM Parts.

Nilfisk Genuine OEM Parts



Patented gas spring technology provides for consistent results regardless of the operator



Simple, one step handle release



Rotomolded body provides lasting durability. Dust bags are easy to access



EZ Store™ construction makes for easy pad changing



EZ Store™ construction allows the Advance Advolution™ 20 and 20XP to be stored in the smallest of cleaning closets

Red SafeStart™ button only allows activation when handle is tilted back for use

Electrically detachable motor for easy service access

75 foot SuperFlex™ safety yellow cord with hospital grade plug

Carbon brush replacement indicator light

Easy access to change dust bags

Rotating cord hook saves time and effort

Maintenance free transmission and direct drive motor

Flexible pad driver

Wrap-around skirt seals tightly to floor to control dust

Technical Specifications

Model	Advolution™ 20	Advolution™ 20XP
Angle Activated Safety Switch	Yes	Yes
Safety Yellow Cord	Yes	Yes
Hospital Grade Plug	Yes	Yes
Maintenance Free Transmission	Yes	Yes
Motor Protection Indicator Light	Yes	Yes
Folding Handle	Yes	Yes
Factory Assembled	Yes	Yes
Sound Level	62.1 dB A	66.5 dB A
Passive Dust Control	No	Yes
Pad Size	20 in (51 cm)	20 in (51 cm)
Pad Speed	1,500 R.P.M.	2,000 R.P.M.
Transmission	Direct Drive	Direct Drive
Construction	Rotomolded	Rotomolded
Motor	1.5 hp	1.5 hp
Cord	75 ft (23 m)	75 ft (23 m)
Height	45.5 in (116 cm)	45.5 in (116 cm)
Width	24 in (61 cm)	24 in (61 cm)
Minimum Depth	16.5 in (42 cm)	16.5 in (42 cm)
Maximum Depth	28 in (71 cm)	32 in (81 cm)
Weight	85 lb (39 kg)	87 lb (39 kg)
Part Number	01510A	01520A

Specifications are subject to change without notice.



Advance

14600 21st Avenue North
Plymouth, MN 55447-3408
www.advance-us.com
Phone: 800-850-5559
Fax: 800-989-6566

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.nilfisk-advance.ca
Phone: 905-564-1149 or 800-668-8400
Fax: 905-564-1030 or 800-263-5111

©2012, Nilfisk-Advance, Inc.,
Printed in U.S.A., Form L3015A, 6-12

