

# AquaPro® XP/H/C

Portable Extractors



# Advance

## FACT SHEET



The Advance AquaPro® series with AquaWand™ represents the ultimate in portable carpet extractors. AquaPro features deep-cleaning power and built-in conveniences to make operators more productive than ever. Each model is equipped with the AquaWand cleaning tool that is light, durable and more efficient than competitive wands.

A key to the exceptional cleaning performance and productivity of the AquaPro series is the AquaWand extraction tool, standard with each model. The rotomolded, low-friction, \*Delrin® glide head on the AquaWand allows it to move effortlessly across carpet. Its laminar airflow design provides increased water pick-up with less time and effort used by the operator. In independent tests, AquaWand left only half as much residual water in carpets as comparable machines. That means better cleaning, faster drying and more time saved.

The AquaPro XP model offers two extraction modes for tough and light jobs. Deep-extraction mode provides 300 psi and 212 degree F solution at the wand tip for superior restoration extraction. With the push of a button, the pressure can be reduced to 75 psi for upholstery or light duty cleaning. This machine has earned the Carpet & Rug Institute's (CRI) Seal of Approval Gold for carpet extraction.

The AquaPro H model also provides the cleaning power of 212 degree F solution at the wand tip, combined with 150 psi for restoration extraction. This model has earned the CRI Seal of Approval Silver for carpet extraction. Both the AquaPro XP and the AquaPro H have an independent circuit locator that identifies when the machine is plugged into separate circuits to prevent blown circuits.

The AquaPro C model is the right choice for lighter jobs. This non-heated, 150 psi model has earned the CRI Seal of Approval Bronze for carpet extraction.

Operators will appreciate the convenience of onboard storage for floor tools and other accessories. All models feature onboard storage of the AquaWand floor tool, self-contained storage for the power cord and a compartment for storing detergent bottles, hand tools and other cleaning items.

Equipped with a 14-gallon solution tank, the AquaPro is large enough to tackle most jobs, yet is compact enough for easy maneuvering and transporting. The solution tank has a clear hose which acts as both a solution gauge and drain hose. The recovery drain hose is designed to easily empty the 12-gallon recovery tank into a commode or slop sink.

Not only does the AquaPro deliver superior cleaning results, but it is also easy to maintain. The clam shell design allows easy access for servicing, and the convenient grips and handle provide assistance when lifting the unit into a vehicle for transport.

### STANDARD FEATURES INCLUDE

- 15 foot Solution Hose
- 15 foot Crush-Proof Recovery Hose
- AquaWand™ Cleaning Tool
- 25 foot Disconnect Power Cord

### TYPICAL APPLICATIONS INCLUDE

- Contract Cleaners
- Educational Facilities
- Office Buildings
- Hotels and Motels
- Healthcare Facilities
- Airports
- Government Buildings



**AquaPro® XP – Gold**  
**AquaPro® H – Silver**  
**AquaPro® C – Bronze**

\* Delrin® is a registered trademark of DuPont

# Advance AquaPro® XP/H/C

## Portable Extractors



The low friction glide and light weight AquaWand is designed for less operator fatigue



Waterproof control panel to protect against spills. The solution tank fill port is recessed to contain spills




Onboard storage of floor tool and chemical bottles or other cleaning tools



Finger grips provide assistance when lifting the machine



Clam shell design allows easy access for servicing



### Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factory-trained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Genuine OEM Parts.

Nilfisk Genuine OEM Parts

## Technical Specifications

	AquaPro® XP	AquaPro® H	AquaPro® C
<b>Solution Pump</b>	300 psi / 75 psi	150 psi	150 psi
<b>Solution Tank Capacity</b>	14 gal (53 L)	14 gal (53 L)	14 gal (53 L)
<b>Recovery Tank Capacity</b>	12 gal (45 L)	12 gal (45 L)	12 gal (45 L)
<b>Vacuum Motors</b>	1 - 3 stage	2 - 2 stage	2 - 2 stage
<b>Built-in Heater</b>	Yes	Yes	No
<b>Waterlift</b>	140 in (356 cm)	150 in (381 cm)	150 in (381 cm)
<b>Air Flow</b>	100 cfm	100 cfm	100 cfm
<b>Solution Hose Length</b>	15 ft (4.5 m)	15 ft (4.5 m)	15 ft (4.5 m)
<b>Recovery Hose Length</b>	15 ft (4.5 m)	15 ft (4.5 m)	15 ft (4.5 m)
<b>Rear Wheels</b>	10 in (25 cm)	10 in (25 cm)	10 in (25 cm)
<b>Front Castors</b>	4 in (10 cm)	4 in (10 cm)	4 in (10 cm)
<b>Power Cord</b>	2 - 25 ft, yellow	2 - 25 ft, yellow	1 - 25 ft, yellow
<b>Length</b>	36 in (91 cm)	36 in (91 cm)	36 in (91 cm)
<b>Width</b>	17 in (43 cm)	17 in (43 cm)	17 in (43 cm)
<b>Height</b>	38 in (96 cm)	38 in (96 cm)	38 in (96 cm)
<b>Machine Weight</b>	115 lb (52 kg)	83 lb (37 kg)	78 lb (35 kg)
<b>Part Numbers</b>	56 380 470	56 380 472	56 380 471

Specifications are subject to change without notice.



14600 21st Avenue North  
Plymouth, MN 55447-3408  
www.advance-us.com  
Phone: 800-850-5559  
Fax: 800-989-6566

240 Superior Boulevard  
Mississauga, Ontario, Canada L5T 2L2  
www.nilfisk-advance.com  
Phone: 905-564-1149 or 800-668-8400  
Fax: 905-564-1030 or 800-263-5111

©2009, Nilfisk-Advance, Inc.,  
Printed in U.S.A., Form L1488A, 12/09

