

Adfinity™ X20C & X20D

Walk-Behind Scrubber



Advance
by Nilfisk-Advance

FACT SHEET



Traction Drive For Increased Productivity.

The new Adfinity™ traction-drive scrubbers from Advance offers the size and performance you need. With a scrub path of 20 inches wide, and an onboard detergent dispensing system, you will get the highest level of cleaning productivity.

If you're looking for a scrubber that offers the most efficient use of cleaning chemicals, an Adfinity with AXP™ is your answer. Advance's patented AXP onboard detergent dispensing system eliminates guesswork by dispensing detergent at the manufacturer's recommended dilution ratio. The Adfinity with AXP eliminates premixing of chemicals, which saves time and prevents detergent and water waste. The Adfinity comes standard with an onboard battery charger, allowing the flexibility to charge the machine at any available electrical outlet.

One-Touch™ operation makes the Adfinity easy to learn and easy to use. The Adfinity is equipped with forward and reverse traction drive and an ergonomic and safe paddle design for extra operator comfort. The Adfinity is designed for easy access to the battery, detergent dispensing system, and the recovery tank.

The Adfinity scrubber is available in 20 inch disc and cylindrical models.

TYPICAL APPLICATIONS INCLUDE

- Auto Dealers
- Beer Distributors
- Manufacturing
- Warehouses
- Hangers

STANDARD FEATURES INCLUDE

- AXP™ Onboard Detergent Dispensing System
- Onboard Battery Charger
- Tools-free removal of squeegee and squeegee blades

OPTIONAL ACCESSORIES INCLUDE

- Variety of Scrub Brushes
- Polyurethane Squeegee Blades
- Integrated Solution Fill Hose
- Hour Meter Kit
- Wet Pick-up Wand Kit
- Scrub and Vac Kit



Advance Adfinity™ X20C & X20D

Walk-Behind Scrubber



Ergonomic and safe paddle system for operator comfort



Easy to use control panel
1. Scrub **2.** Vacuum
3. Pad drive click-off
4. AXP™ on/off; set dilution rate at control panel



Tools-free removable brushes



Access to batteries and AXP onboard dispensing system



Industrial Strength Solutions...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factory-trained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Genuine OEM Parts.

Nilfisk Genuine OEM Parts

Technical Specifications

| Models | Adfinity™ X20D | Adfinity™ X20C |
|---|---|---|
| Scrub Head Type | Disc 20 in (50.8 cm) | Cylindrical with debris hopper |
| Deck Interchangeability | All deck types interchangeable – ALL MODELS | |
| Scrub Path | 20 in (50.8 cm) disc brush system | Dual 20 in (50.8 cm) cylindrical brush system |
| Drive System | 0.3 hp (200 W) variable forward and reverse Max speed 3.5 mph (5.6 km/hr), 16% gradeability – ALL MODELS | |
| Max Productivity @ 3.0 mph (4.8 km/hr) | 26,400 ft ² (2,453 m ²) | 26,400 ft ² (2,453 m ²) |
| Scrub Pressure (2 settings) | | |
| Floating | 50 lb (25 kg) | 57 lb (26 kg) |
| Locked | 70 lb (32 kg) | – |
| Scrub Head Speed | 170 rpm | 570 rpm |
| Solution Flow Rates | | |
| Smart Solutions™ variable up to | 0.15 gal/min (0.55 L/min) – ALL MODELS 0.3 gal/min (1.1 L/min) – ALL MODELS | |
| Squeegee Width | 29.9 in (75.9 cm) | 29.9 in (75.9 cm) |
| Dimensions (w/o squeegee) | L = 52 in (132 cm) W = 21.3 in (54 cm) H = 42.9 in (109 cm) | L = 49.2 in (125 cm) W = 22.4 in (57 cm) H = 42.9 in (109 cm) |
| Weights | | |
| Without batteries | 244 lb (111 kg) | 247 lb (112 kg) |
| With batteries | 350 lb (159 kg) | 362 lb (164 kg) |
| Voltage | 24 V – ALL MODELS | |
| Power Source | (2) 12 V batteries (wet-acid and maintenance free available) – ALL MODELS | |
| Onboard Battery Charger | 24 V wet/maintenance free compatible – ALL MODELS | |
| Solution Tank | 14.5 gal (55 L) – ALL MODELS | |
| Recovery Tank | 14.5 gal (55 L) – ALL MODELS | |
| Scrub Motor(s) | 0.65 hp (480 W) | (2) 0.54 hp (400 W) |
| Vacuum Motor | 0.44 hp (330 W) – ALL MODELS | |
| Sound Level | 65.8 dB A at operator's position – ALL MODELS | |
| Approvals | ETL, CSA, CE – ALL MODELS | |
| Certification | NFSI | |
| Part Number | 56317335 w/130 Ah wet-acid batt. 56317336 w/98 Ah gel batt. | 56317331 w/130 Ah wet-acid batt. 56317332 w/98 Ah gel batt. |

Specifications are subject to change without notice.



14600 21st Avenue North
 Plymouth, MN 55447-3408
 www.advance-us.com
 Phone: 800-214-7700
 Fax: 800-989-6566

240 Superior Boulevard
 Mississauga, Ontario, Canada L5T 2L2
 www.nilfisk-advance.com
 Phone: 905-564-1149 or 800-668-8400
 Fax: 905-564-1030 or 800-263-5111

©2008, Nilfisk-Advance, Inc.,
 Printed in U.S.A., Form L3020A, 12-08

